

Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 1/_13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Helium, compressed

Trade name: Helium Balloon Gas, Fill'N'Away, Helium

Additional identification

Chemical name: Helium

Chemical formula: He INDEX No. -

CAS-No. 7440-59-7 **EC No.** 231-168-5

REACH Registration No. Listed in Annex IV/ V of Regulation (EC) No 1907/ 2006 (REACH), exempted

from registration.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.

Balance gas for mixtures. Balloon gas. Calibration gas. Carrier gas. Combustion, melting and cutting processes. Inerting gas. Laboratory use. Laser gas. Pressure head gas, operational assist gas in pressure systems.

Process gas. Professional diving. Purge gas. Test gas.

Consumer use.

Balloon gas. Shielding gas in gas welding.

Uses advised against Industrial or technical grade unsuitable for medical applications or inhalation.

Inhaling helium may cause asphyxiation followed by death.

1.3 Details of the supplier of the safety data sheet Supplier

Adams Gas **Telephone:** 0044 1843 220596

Strasbourg Street, Westwood Industrial

Estate

Margate, Kent, UK, CT9 4JF

E-mail: in fo@adamsgas.co.uk

1.4 Emergency telephone number: 0044 1843 220596

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC as amended.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 2/_13

Not classified

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Gases under pressure Compressed gas H280: Contains gas under pressure;

may explode if heated.

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H280: Contains gas under pressure; may explode if heated.

Precautionary Statement

Prevention: None.

Response: None.

Storage: P403: Store in a well-ventilated place.

Disposal: None.

Supplemental label information

EIGA-As: Asphyxiant in high concentrations.

2.3 Other hazards: None.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name Helium INDEX No.: -

CAS-No.: 7440-59-7 **EC No.:** 231-168-5

REACH Registration No.: Listed in Annex IV/ V of Regulation (EC) No 1907/ 2006 (REACH), exempted from

registration.

Purity: 100%

The purity of the substance in this section is used for classification only and does not represent the actual purity of the substance as supplied, for which other

documentation should be consulted.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 3/_13

Trade name: Helium Balloon Gas, Helium, Fill'N'Away

SECTION 4: First Aid Measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/ consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing

stopped.

4.1 Description of first aid measures

Inhalation:

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/ consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self-contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing

stopped.

Eye contact:

Adverse effects not expected from this product.

Skin Contact:

Adverse effects not expected from this product.

Ingestion:

Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and

effects, both acute and delayed:

Respiratory arrest.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: None.

Treatment: None.

SECTION 5: Firefighting Measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Material will not burn. In case of fire in the surroundings: use appropriate

extinguishing agent.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the

substance or mixture:

None.



Issue Date: Version: 2 20/11/2014

Last revised date: 01/01/2021 4/13

Hazardous Combustion Products: None.

5.3 Advice for firefighters

Special firefighting procedures: In case of fire: Stop leak if safe to do so. Continue water spray from protected

position until container stays cool. Use extinguishants to contain the fire.

Isolate the source of the fire or let it burn out.

Special protective equipment Firefighters must use standard protective equipment including flame retardant for firefighters: coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for firefighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and

emergency procedures:

Evacuate area. Provide adequate ventilation. Prevent from entering sewers, basements and work pits, or any place where its accumulation can be

dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Guideline EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with

full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation.

6.4 Reference to other sections: Refer to sections 8 and 13.

SECTION 7: Handling and Storage:



Version: 2 Issue Date: 20/11/2014

Last revised date: 01/01/2021 5/13

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier

identification of the container contents. When moving containers, even for short distances, use appropriate equipment e.g. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow back feed into the container. Avoid suck back of water, acid and alkalis. Keep container below 50°C in a well-ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/ national/ international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

including any incompatibilities:

7.2 Conditions for safe storage, Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure Controls/ Personal Protection

8.1 Control Parameters Occupational Exposure Limits

None of the components have assigned exposure limits.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 6/_13

8.2 Exposure controls

Appropriate engineering controls: Consider a work permit system e.g. for maintenance activities. Ensure adequate

air ventilation. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Preferably use permanent leak tight connections (e.g. welded pipes). Do not

eat, drink or smoke when using the product.

Individual protection measures, such as personal protective equipment

General information: A risk assessment should be conducted and documented in each work area to

assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self-contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected

based on the task being performed and the risks involved.

Eye/face protection: Wear eye protection to EN 166 when using gases.

Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection: Wear working gloves while handling containers

Guideline: EN 388 Protective gloves against mechanical risks.

Body protection: No special precautions.

Other: Wear safety shoes while handling containers

Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection: Not required.

Thermal hazards: No precautionary measures are necessary.

Hygiene measures: Specific risk management measures are not required beyond good industrial

hygiene and safety procedures. Do not eat, drink or smoke when using the

product.

Environmental exposure

controls:

For waste disposal, see section 13.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties Appearance

Physical state: Gas

Form: Compressed gas
Colour: Colourless



SAFETY DATA SHEET

Helium, compressed

Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 7/_13

Odour: Odourless

Odour Threshold: Odour threshold is subjective and is inadequate to warn of

over exposure.

pH: not applicable.Melting Point: -272.15 °CBoiling Point: -269 °C

Sublimation Point: not applicable.

Critical Temp. (°C): -268.0 °C

Flash Point: Not applicable to gases and gas

mixtures.

Evaporation Rate: Not applicable to gases and gas

mixtures.

Flammability (solid, gas): This product is not flammable.

Flammability limit - upper (%): not applicable.
Flammability limit - lower (%): not applicable.

Vapour pressure: No reliable data available.

Vapour density (air=1): 0.138 (0 °C)

Relative density: No data available.

Solubility(ies)

Solubility in Water: 2.5 mg/ l (21 °C)

Partition coefficient (n-octanol/water): Not known.

Autoignition Temperature: not applicable.

Decomposition Temperature: Not known.

Viscosity

Kinematic viscosity:

Dynamic viscosity:

0.025 mPa.s

Explosive properties:

Not applicable.

Oxidising Properties:

not applicable.

9.2 Other information: None.

Molecular weight: 4 g/ mol (He)

SECTION 10: Stability and Reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of Hazardous

Reactions:

None.

10.4 Conditions to Avoid: None.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 8/_13

10.5 Incompatible Materials: No reaction with any common materials in dry or wet conditions.

10.6 Hazardous Decomposition Under normal conditions of storage and use, hazardous decomposition products

Products: should not be produced.

SECTION 11: Toxicological Information

General information: None.

11.1 Information on toxicological effects

Acute toxicity - Oral

Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal

Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation

Product Based on available data, the classification criteria are not met.

Skin Corrosion/Irritation

Product Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation

Product Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitisation

Product Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product Based on available data, the classification criteria are not met.

Carcinogenicity

Product Based on available data, the classification criteria are not met.

Reproductive toxicity

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product Based on available data, the classification criteria are not met.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> 01/01/2021 9/ 13

Aspiration Hazard

Product Not applicable to gases and gas mixtures..

SECTION 12: Ecological Information

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures.

12.3 Bio accumulative Potential

Product The product is expected to biodegrade and is not expected to persist for long periods in an aquatic

environment.

12.4 Mobility in Soil

Product Because of its high volatility, the product is unlikely to cause ground or water

pollution.

12.5 Results of PBT and vPvB assessment

Product Not classified as PBT or vPvB.

12.6 Other Adverse Effects: No ecological damage caused by this product.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

General information: Do not discharge into any place where its accumulation could be dangerous. Vent

to atmosphere in a well-ventilated place.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to

national, state, or local laws.

European Waste Codes

Container:

16 05 05: Gases in pressure containers other than those mentioned in 16 05

04

SECTION 14: Transport

Information



SAFETY DATA SHEET

Helium, compressed

Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 10/_13

ADR

14.1 UN Number: UN 1046 14.2 UN Proper Shipping Name: HELIUM,

COMPRESSED

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.2
Hazard No. (ADR): 20
Tunnel restriction code: (E)
Emergency Action Code: 2T
14.4 Packing Group: -

14.5 Environmental hazards: not applicable

14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1046
14.2 UN Proper Shipping Name HELIUM,
COMPRESSED

14.3 Transport Hazard Class(es)

Class: 2
Label(s): 2.2
14.4 Packing Group: -

14.5 Environmental hazards: not applicable

14.6 Special precautions for user: –

IMDG

14.1 UN Number: UN 1046
14.2 UN Proper Shipping Name: HELIUM,
COMPRESSED

14.3 Transport Hazard Class(es)

 Class:
 2.2

 Label(s):
 2.2

 EmS No.:
 F-C, S-V

14.3 Packing Group: -

14.5 Environmental hazards: not applicable

14.6 Special precautions for user: —

IATA

14.1 UN Number: UN 1046

14.2 Proper Shipping Name: Helium, compressed

14.3 Transport Hazard Class(es):

Class: 2.2
Label(s): 2.2
14.4 Packing Group: -

14.5 Environmental hazards: not applicable



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> 01/01/2021 11/13

14.6 Special precautions for user:

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from

the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure

adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

National Regulations

Management of Health and Safety at Work Regulations (1999 No. 3242). The Regulatory Reform (Fire Safety) Order 2005 (2005 No. 1541). Control of Substances Hazardous to Health Regulations (COSHH, 2002 No. 2677). Provision and Use of Work

Equipment Regulations (PUWER, 1998 No. 2306). Personal Protective Equipment Regulations (1992 No. 2966). Control of Major Accident Hazards Regulations (COMAH, 2015 No. 483). Pressure Systems Safety Regulations (PSSR, 2000 No. 128). Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No.

231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 453/

2010.

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other Information

Revision Information: Not relevant.



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 12/_13

Key literature sources for data:

references

and Various sources of data have been used in the compilation of this SDS, they include

but are not exclusive to:

Agency for Toxic Substances and Diseases Registry (ATSDR) (http:/

/www.atsdr.cdc.gov/).

European Chemical Agency: Guidance on the Compilation of Safety Data Sheets. European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search

European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.

International Programme on Chemical Safety (http://www.inchem.org/) ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.

Matheson Gas Data Book, 7th Edition.

National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.

The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).

The European Chemical Industry Council (CEFIC) ERICards.

United States of America's National Library of Medicine's toxicology data network TOXNET (http://toxnet.nlm.nih.gov/index.html)

Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).

Substance specific information from suppliers.

Details given in this document are believed to be correct at the time of publication. EH40 (as amended) Workplace exposure limits.

Wording of the R-phrases and H-statements in sections 2 and 3

H280 Contains gas under pressure; may explode if heated.

Training information: Users of breathing apparatus must be trained. The hazard of asphyxiation is often overlooked and must be stressed during operator training. Ensure operators understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Press. Gas Compr. Gas, H280

Other information:

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/ local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. Note: When the Product Name appears in the SDS header the decimal sign and its position comply with rules for the structure and drafting of international standards and is a comma on the line. As an example, 2,000 is two (to three decimal places) and not two thousand, whilst 1.000 is one thousand and not one (to three decimal places).

Last revised date: 01/06/2018



Issue Date: 20/11/2014 Version: 2

<u>Last revised date:</u> <u>01/01/2021</u> 13/13

Disclaimer: This information is provided without warranty. The information is believed to be

correct. This information should be used to make an independent determination of $% \left\{ 1\right\} =\left\{ 1\right\} =\left$

the methods to safeguard workers and the environment.