## **SLICE®** Complete Pack

## Exothermic portable cutting pack complete with it's own ignition source





SLICE Complete Pack

Go anywhere and cut, burn, or pierce virtually any metallic, non-metallic or composite material with this exothermic cutting pack.

A self-contained cutting system lends itself well to the emergency / forced entry type cutting situations where seconds count.

- Improved torch handle & rubber shield to improve the operators grip and provide protection from molten spray when piercing
- Improved striker assembly that incorporates a slide mechanism that allows the operator to only expose a small portion of the ignition bar (copper) which increases the life of the striker copper bar
- Improved battery box with improved features over prior model
  - Faster recharging of a "dead" battery
  - Better visual "gas gauge" indicating battery condition
  - Over-charging safe guard

Visit **esab.com** for more information.

## **Industry**

- Bridge Construction
- Industrial and General Fabrication
- Mining
- Repair and Maintenance
- Steel Erectors



## **SLICE®** Complete Pack

| Specifications                        |   |
|---------------------------------------|---|
| Main Voltage (Input)                  | 120 V AC 60 Hz & 220 VAC 50 Hz                              |
| Output Voltage                        | 12 V DC   |
| Recharge Time (fully drained battery) | 6 h   |
| Exothermic Cutting Rods               | 1/4 in. x 22 in. Uncoated – 25 pieces                       |
| Length Of Power Cable & Oxygen Hose   | 3 m (10 ft.)  |
| Power Cable AWG Size                  | #10   |
| Certification Mark (Standards)        | CE  |
| Dimensions L x W H (Without Cylinder) | 400.05 mm x 638.18 mm x 206.38 mm (15 in. x 25 in. x 8 in.) |
| Dimensions L x W H (With Cylinder)    | 400.05 mm x 688.98 mm x 206.38 mm (15 in. x 27 in. x 8 in.) |
| Weight Without Cylinder               | 17.71 kg (39.05 lbs.)                                       |
| Weight With Cylinder                  | 31.75 kg (70 lbs.)  |

| Ordering Information                 |            |
|--------------------------------------|------------|
| SLICE Complete Pack – 220 V AC 50 Hz | 63991042CE |

| Options and Accessories  |              |
|--|--------------|
| SLICE Battery Ignition Source  | 96-076-040   |
| Power Adapter w/ Europe Power Lead   | 96-076-042   |
| SLICE Cutting Torch CE w/ #10 Power Cable (When Igniting w/ 12V Battery & Cutting w/o Power) | 03-003-012CE |
| SLICE Cutting Torch CE w/ #6 (When Igniting 12V Battery & Cutting w/o Power)                 | 03-003-011CE |
| SLICE Cutting Torch CE w/ #1 (Up to 200 A w/ Power)  | 03-003-010CE |
| SLICE Striker Assembly   | 72-012-010   |

| Cutting Rods   |          |
|--|----------|
| SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 100 Pcs | 42049003 |
| SLICE Exothermic Cutting Rods, Flux Coated, 1/4 x 22 - 25 Pcs  | 42049002 |
| SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 36 - 25 Pcs     | 43049009 |
| SLICE Exothermic Cutting Rods, Uncoated, 3/8 x 18 - 50 Pcs     | 43049007 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 25 Pcs     | 43049002 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 44 - 25 Pcs     | 43049005 |
| SLICE Exothermic Cutting Rods, Flux Coated, 3/8 x 18 - 50 Pcs  | 42049005 |
| SLICE Exothermic Cutting Rods, Uncoated, 1/4 x 22 - 100 Pcs    | 43049003 |

ESAB / esab.com









GLOBALLY CERTIFIED MANAGEMENT SYSTEMS