

Protex Original

Anti spatter surface protector



Protex Original reduces spatter and protects from slag spoiling clean edges. Protects the parent metal, fixtures, large weldments and jigs from spatter and slag. Use it during heat treating to protect surfaces from scale. Easy to brush on, or dip in, quick drying, will not blow off with air blast, is easily removed, remains effective for successive passes.

Use Protex Original any time where a clean finish is desired, cutting down on finishing time and removing the need for extra grinding.

- Easy to use
- Non-toxic
- Non-flammable
- Greater coverage
- Dries fast
- Environmentally safe
- Easy clean-up

Visit esab.com for more information.

Industry

- Foundries
- Ship/Barge Building
- Light Equipment
- Heavy Equipment
- Industrial Production & Manufacturing

Left: Spatter sticks to untreated plate and cannot be removed
Right: Protex Original allows spatter to be easily brushed away



Specifications

Volume	3.8 L (1 Gal), 19 L (5 Gal), 208 L (55 Gal), 833 L (220 Gal)
Appearance	Pink, Slurry
Odor	Slight Chemical Odor
PH Value	Slightly Alkaline
Solubility	Water Soluble

Ordering Information

Arcair Protex Original, 3.8 L (1 gal) per unit – Case of 4	53-011-000
Arcair Protex Original, 19 L (5 Gal)	53-015-000
Arcair Protex Original, 208 L (55 Gal)	53-018-000
Arcair Protex Original, 833 L (220 Gal)	53-019-000



ESAB / esab.com

