



ø 300mm (20kg)



320 x 480 TFT



240V/110V



550V Tested in production



Voltage Reduction Device



MCU control system



Spool Gun



Moisture ✓ Salt spray ✓ Corrosion ✓



Generator friendly

Stealth

Machines

9015H Digi-Multi Mig 200 Pro 4-in-1 Multi-process

FEATURES

- Multiple process with just one machine
- Compact and complete
- Direct selection of SYN parameters and intuitive setting of parameters can increase efficiency and productivity

PROCESS

- MIG SYN
- MIG MANUAL
- TIG AC PULSE (LIFT TIG/HF TIG)
- TIG DC PULSE (LIFT TIG/HF TIG)
- STICK AC
- STICK DC



SPECIFICATIONS

Input power voltage (V)	110/230±10%		
Frequency (Hz)	50/60		
	MIG	TIG	MMA
Effective current – 110V	20.5	19.8/19.3 (AC/DC)	19.2/20.2 (AC/DC)
Effective current – 230V	15.4	12.2/12.1 (AC/DC)	15.2/16.7 (AC/DC)
Duty cycle (A) (40°C 10 min) – 110V	30% @ 200 60% @ 145 100% @ 110	30% @ 200 60% @ 145 100% @ 110	30% @ 200 60% @ 145 100% @ 110
– 220V	30% @ 140 60% @ 100 100% @ 80	30% @ 160 60% @ 115 100% @ 90	25% @ 130 60% @ 85 100% @ 65
No load voltage – limited (V)	72V		
Welding current range (A) – 110V	30~140	10~160	10~130
– 230V	30~200	10~200	10~200
Welding voltage range (V) – 110V	15.5~21	10.4~16.4	20.4~25.2
– 230V	15.5~24	10.4~18	20.4~28
Efficiency (%)	80		
Power factor	0.99		
Insulation class	H		
Protection class	IP21S		
Cooling	Air		
Overall dimensions (mm)	610 x 220 x 410		
Weight (kg)	21		
Accessories included	3m Argon hose, 3m earth return lead		

ACCESSORY KIT

9862H

Air Cooled Tig Package consisting of:

- ET17-12SZ Torch
- WP17AK Accessory Kit
- D3595-1-1 Tig Adaptor
- WE25/12 12 Pin Plug (Pins 2 & 3)