



Metal guard system supplied as part of a comprehensive kit package



The MAX40V offers a 145mm stroke and comfortably accommodates cutters up to 110mm for deep broaching. It also accepts the VersaDrive Rapid-Lock Weldon Adapter with VersaDrive tooling, opening up 1,000s of time saving solutions from the whole VersaDrive system.

## Technical Specifications

|                      |                          |
|----------------------|--------------------------|
| CUTTER SIZE RANGE    | 12 - 40mm TCT            |
| MAX CUTTER LENGTH    | 110mm                    |
| TWIST DRILL CAPACITY | 16mm                     |
| COUNTERSINKING       | 25mm                     |
| REAMING              | 12mm                     |
| LENGTH               | 264mm                    |
| WIDTH (Inc Handles)  | 180mm                    |
| HEIGHT (Min-Max)     | 360 - 440mm              |
| STROKE               | 145mm                    |
| WEIGHT               | 10.5 kg                  |
| MAGNET (L X W)       | 160 x 80mm               |
| MAGNETIC ADHESION    | 1500 kgs                 |
| MOTOR POWER          | 1150w                    |
| SPEED RPM (No Load)  | 600 RPM                  |
| SPINDLE              | 19.05 mm (3/4") Weldon   |
| COOLANT SYSTEM       | Gravity Oil Fed          |
| WARRANTY             | 2 Year (When registered) |

MARKET LEADING PERFORMANCE

| Part No    | Contents                            |
|------------|-------------------------------------|
| 803046-110 | HMT MAX40V<br>Magnetic Drill - 110V |
| 803046-230 | HMT MAX40V<br>Magnetic Drill - 230V |