

Extractability™

PRODUCT INFORMATION

ProtectoBench 1000/1500/2000/2500

SUMMARY

ProtectoBench 1000/1500/2000/2500 is a downdraught extraction bench with optional backdraught extraction. Protectobench is supplied to sit on the floor. The extraction bench removes hazardous smoke and dust at source.

Fumes & dust are extracted downwards and also to the back wall if this option is fitted. 90% of the extracted particles are pre-separated within the bottom section of the bench which can then be disposed by means of emptying the dust tray. ProtectoBench requires fan & filter system to be connected.

TARGET APPLICATIONS

Welding and grinding alloyed and unalloyed steels, precious metals, galvanised material.



FURTHER INFORMATION

Optional rear wall extraction, side panels, lamella curtain folding sides, wood supports.

ARTICLES & ACCESSORIES

Part Number	
PROTECTOBENCH1000	1m wide
PROTECTOBENCH1500	1.5m wide
PROTECTOBENCH2000	2m wide
PROTECTOBENCH2500	2.5m wide
EXT999200005	Lamella Sides

TECHNICAL SPECIFICATION

Extraction Capacity	Bench 1000 = 1500 m ³ /h Bench 1500 = 1800 m ³ /h Bench 2000 = 2300 m ³ /h Bench 2500 = 3000 m ³ /h
Rear Extraction	Bench 1000 = 150mm diameter Bench 1500 = 150mm diameter Bench 2000 = 2 x 150mm diameter Bench 2500 = 2 x 150mm diameter
Low Level Extraction	Bench 1000 = 180mm diameter Bench 1500 = 200mm diameter Bench 2000 = 224mm diameter Bench 2500 = 250mm diameter
Dimensions (LxWxH)	1000m x 1000mm x 850mm 1500m x 1000mm x 850mm 2000m x 1000mm x 850mm 2500m x 1000mm x 850mm Back Wall & Sides 900mm (H ONLY)

For further information, contact Extractability technical support on **0845 862 2620** or email service@extractability.eu