

# Extractability™

## PRODUCT INFORMATION

### SPARK LATCH

#### SUMMARY

The spark latch consists of a separate housing with integrated copper plates. The assembly of the copper plates guarantees a multiple air scoop. Due to this, sparks bump into the baffle plates and emit their energy.

#### TARGET APPLICATIONS

Applications: Pre-separation of hot sparks prior to ductwork connection to filter systems. Reduces the risk of filter media catching on fire.



#### FURTHER INFORMATION

The spark latch can be screwed to the filter unit or it can also be integrated into the suction ducting. By means of a maintenance trays, the spark latch can be cleaned if necessary.

#### ARTICLES & ACCESSORIES

Part Number	Product Description
EXT95014901601	Spark Latch 160mm diameter
EXT9501490200005	Spark Latch 200mm diameter
EXT95149224	Spark Latch 224mm diameter
EXT95014902501	Spark Latch 250mm diameter
EXT9501490280	Spark Latch 280mm diameter
EXT950149031505	Spark Latch 315mm diameter
EXT95014935510	Spark Latch 355mm diameter
EXT95014940010	Spark Latch 400mm diameter

#### TECHNICAL SPECIFICATION

Dimension	370 x 415 x 370 mm
Duct Diameter Range	160, 200, 224, 250, 315, 355, 400mm
Baffle Plates	Copper
Colour	Red
Weight	17kg

For further information, contact Extractability technical support on **0845 862 2620** or email [service@extractability.eu](mailto:service@extractability.eu)