

# Extractability™

## PRODUCT INFORMATION

### PVC FABRIC REINFORCED DUCTING

#### SUMMARY

Double ply flame retardant PVC coated polyester fabric with an encapsulated spring steel wire helix.  
Colour: Black

#### TARGET APPLICATIONS

Applications: Extraction of air, dust, welding fumes and air conditioning.



#### FURTHER INFORMATION

Standard Length: 10 Metres  
Diameter Range: 100, 125, 156, 160, 200, 250mm  
Temperature Range: -30°C to +80°C in a 20°C ambient (Intermittent to 100°C).

#### ARTICLES & ACCESSORIES

Part Number	Product Description
EXTPVC100	10m Extraction Hose 100mm
EXTPVC125	10m Extraction Hose 125mm
EXTPVC150	10m Extraction Hose 150mm
EXTPVC160	10m Extraction Hose 160mm
EXTPVC200	10m Extraction Hose 200mm
EXTPVC250	10m Extraction Hose 250mm

#### TECHNICAL SPECIFICATION

Standard Length	10 Metres
Diameter Range	100, 125, 156, 160, 200, 250mm
Temperature Range	: -30°C to +80°C in a 20°C ambient (Intermittent to 100°C).
Colour	Black

For further information, contact Extractability technical support on **0845 862 2620** or email [service@extractability.eu](mailto:service@extractability.eu)