

9008H DIGI-MIG 250-3 PHASE Multiprocess Single/Dual Pulse



550V
Tested in
production



Heavy Duty
Cycle



Phase
Loss
Protection



3 Phase
400V



Synergic



Generator
friendly

FEATURES

- Devoted pulse curves activate for aluminium, mild steel, stainless steel and CuSi3
- Waveform control for added stability of the arc – even at low currents
- Variable amperage control with digital meter for simultaneous welding current and voltage display
- Equipped with temperature, voltage and current sensors for high protection
- Optional trolley and water cooling unit
- M25-3 torch and regulator included

SPECIFICATIONS

Input power voltage (V)	3~400		
	MIG	TIG	MMA
Maximum (KVA)	10.5	9.2	12.6
Effective input current (A)	14.0	12.5	15.5
Duty cycle (A) (40°C 10 min)	60% @ 250		
	100% @ 195		
Maximum no-load voltage (V)	15 (MMA)		
Welding current range (A)	15~250	10~250	10~250
Protection class	Ip23		
Efficiency (%)	80		
Insulation class	H		
Cooling	Air		
Overall dimensions (mm)	670 x 240 x 450		
Weight (kg)	26		
Accessories included	3m Argon hose + Amphenol plug		
	3m earth return lead		
	3m electrode lead		

